

SS-VS-CASE Video System in Pelicase

Video System in Pelicase

Designed to tackle the challenges of Nordic conditions, the SS-VS-CASE is a sturdy and dependable recording solution. Its robust build ensures durability, making it a reliable choice.

Operating the SS-VS-CASE is intuitive with just four buttons to control record, pause, stop, and snapshot functions. For more advanced features such as text overlay, on-screen date/time, project naming, and playback/backup, you can effortlessly manage them using either a mouse and keyboard or simply a mouse with its integrated on-screen keyboard.

The system uses an SSD to store all recordings, either in a continues video, the system has a cyclic storage function so older recordings will be deleted if it runs out of space during the operation.

Easily access and review past recordings using the calendar overview feature. Plus, with upgradable storage options, you can customize the device to suit your needs perfectly.

The SS-VS-CASE also offers some nice touches, like a customizable boot logo and 2-stage light control for added convenience. It's a practical and user-friendly solution for your recording needs, delivering reliable performance without unnecessary complexity.





Features:

- 2-Stage light control 100% / 50%
- Buttons to control the unit, Record, Pause, Stop, Snapshot
- Text overlay, Date/time, Project name/Description, Company name, comment function (Add comments that shows up in the recording for a set amount of time.
- Easily navigated playback function, with the possibility to take snapshots.
- Upgradable storage if required.
- Intuitive, easy to use backup function. Transfer need snapshots/recordings to an external storage device if needed.
- Add multiple users with different levels of access, customizable permissions for all users of the system.
- Navigate the interface either with a mouse and an on-screen keyboard or a mouse/keyboard combination.
- Combined with SS-UWK-HD-01, internal camera functions can be controlled with a on screen navigation menu, giving you the option to set the camera to your exact specifications.

Applications:

- Commercial Diving
- CCTV Systems
- Fixed installations
- Dropdown systems
- ROV systems







Specifications:

Connectors	SS-VS-CASE
Channels	1
Light Control	Ampere regulated(max1.7A)
Camera control	Balanced or Unbalanced(settable)
Control	Direct voltage control
DVR Screen size	
Power Supply	12-35 vdc (22 watt)
Depth Data (optional)	Depth sensor pass-through
Material Frontglass	Polycarbonate (Lexan)
Connectors	
Umbilical	Amphenol 10PIN Chassis
Battery/Power	
Run time	20-45min
Charging time	12hours
Power Supply	12-35 vdc (22 watt)

Accessories:







SS-DS-01 SS-UWK-HD-01 SS-UW-Ø35